

KOMPAC TECHNICAL UPDATE

NO: 63
DATE: APRIL 1997
**TO: ALL KOMPAC
DEALERS**
**SUBJECT: KOMPAC
CLEANING
SEALS**

**The weekly use of Kompac Cleaning Seals
will prolong roller and seal life and reduce
hickeys caused by dried ink residue!!!**

Upon completion of your end of week deglazing and maintenance routine:

STEP 1. Make sure your Kompac unit is clean and dry! Remove the teflon seals and clean them with Wash V-120 or other water miscible wash. Insert the **KOMPAC CLEANING SEALS**, dry. Close seal spring.

STEP 2. Saturate the Cleaning Seals with Wash V-120 or other water miscible wash, mixed with 25% water. **Note:** Be careful not to over saturate the Cleaning Seals, as excess wash will drip into press! Replace the Kompac unit cover or safety guards and run the Kompac unit for 2 minutes, maximum!

STEP 3. Stop the press, remove the Kompac cover and remove the **KOMPAC CLEANING SEALS**. *Note the dried ink accumulated on the Cleaning Seals. Reinstall the Teflon seals.

NOTE:

- One set of Cleaning Seals can be used twice, just reverse them for the 2nd cleaning.
- There are two versions of the **KOMPAC CLEANING SEALS**, one for **Kompac II** units (Teflon Seal **P/N 92370**) and one for **Kompac III** units (Teflon Seal **P/N 90850**).
- Dispose of used Cleaning Seals in accordance with local regulations.
- Do not use Cleaning Seals more than two times!
- Weekly use of Kompac Cleaning Seals does not eliminate the need for daily Kompac maintenance (See Kompac Maintenance Manual).

TO ORDER:

KOMPAC II CLEANING SEALS - USE PART # 93930 (GREY)

KOMPAC III CLEANING SEALS - USE PART # 94900 (WHITE)

KOMPAC CLEANING SEALS ARE SOLD 12 SETS PER UNIT (24 SEALS), APPROXIMATELY A HALF YEAR SUPPLY.

SUGGESTED RETAIL PRICE

PART # 93930 - \$18.85

PART # 94900 - \$20.95

DEALER COST

\$12.82

\$14.25

Michael Pek
Technical Representative, Kompac Division